

SHIPLEY -- MICROPOSIT REMOVER 1165
MATERIAL SAFETY DATA SHEET
NSN: 801000N056395
Manufacturer's CAGE: 0AS27
Part No. Indicator: A
Part Number/Trade Name: MICROPOSIT REMOVER 1165

=====
General Information
=====

Company's Name: SHIPLEY CO INC
Company's Street: 455 FOREST ST
Company's City: MARLBOROUGE
Company's State: MA
Company's Country: US
Company's Zip Code: 01752
Company's Emerg Ph #: 800-424-9300(CHEMTREC)
Company's Info Ph #: 508-481-7950
Record No. For Safety Entry: 001
Tot Safety Entries This Stk#: 001
Status: SMJ
Date MSDS Prepared: 27FEB92
Safety Data Review Date: 29DEC94
MSDS Preparer's Name: T. BLAKESLEE
Preparer's Company: SAME
MSDS Serial Number: BWFYL
Hazard Characteristic Code: NK

=====
Ingredients/Identity Information
=====

Proprietary: NO
Ingredient: 2-PYRROLIDINONE, 1-METHYL-; (N-METHYL-2-PYRROLIDONE)
Ingredient Sequence Number: 01
Percent: 95
NIOSH (RTECS) Number: UY5790000
CAS Number: 872-50-4
OSHA PEL: N/K (FP N)
ACGIH TLV: N/K (FP N)

Proprietary: NO
Ingredient: NON-HAZARDOUS INGREDIENTS
Ingredient Sequence Number: 02
Percent: 5
NIOSH (RTECS) Number: 1000314NH
OSHA PEL: N/K (FP N)
ACGIH TLV: N/K (FP N)

=====
Physical/Chemical Characteristics
=====

Appearance And Odor: WATER WHITE LIQUID W/MILD AMINE ODOR.
Boiling Point: 396F,202C
Vapor Pressure (MM Hg/70 F): 0.5 @ 25C
Vapor Density (Air=1): 3.4
Specific Gravity: 1.03
Evaporation Rate And Ref: SLOWER THAN ETHER
Solubility In Water: COMPLETE
Percent Volatiles By Volume: SUPDAT
pH: N/A

=====
Fire and Explosion Hazard Data
=====

Flash Point: 190F,88C
Flash Point Method: PMCC
Lower Explosive Limit: 0.99%
Extinguishing Media: ALCOHOL FOAM, CARBON DIOXIDE, DRY CHEMICAL.
Special Fire Fighting Proc: USE NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT (FP N). CONTAINERS NEAR FIRE MAY BE COOLED W/WATER.
Unusual Fire And Expl Hazrds: PRESSURE MAY BUILD UP IN CLOSED CONTAINERS. THIS IS ACCELERATED BY HEAT W/POSSIBLE LIBERATION OF COMBUSTIBLE VAPORS.
=====

=====
Reactivity Data
=====

Stability: YES
Cond To Avoid (Stability): HEAT, SPARKS, FLAME.
Materials To Avoid: STRONG ACIDS, OXIDANTS.
Hazardous Decomp Products: UPON THERMAL DECOMPOSITION MAY EMIT TOXIC FUMES, INCLUDING CARBON MONOXIDE & NITROGEN OXIDES.
Hazardous Poly Occur: NO
Conditions To Avoid (Poly): NOT RELEVANT
=====

=====
Health Hazard Data
=====

LD50-LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.
Route Of Entry - Inhalation: YES
Route Of Entry - Skin: YES
Route Of Entry - Ingestion: YES
Health Haz Acute And Chronic: ACUTE:EYE & SKIN CONTACT CAN CAUSE IRRITATION, ITCHING, REDNESS, TEARING, BURNING, INFLAMMATION. INHALATION, INGESTION & SKIN ABSORPTION CAN CAUSE IRRITATION, HEADACHE, NAUSEA, VOMITING, CONFUSION, GIDDINESS. CHRONIC:PROLONGED, REPEATED CONTACT W/SKIN CAN CAUSE ITCHING, REDNESS, TEARING, BURNING, (EFTS OF OVEREXP)
Carcinogenicity - NTP: NO
Carcinogenicity - IARC: NO
Carcinogenicity - OSHA: NO
Explanation Carcinogenicity: NOT RELEVANT
Signs/Symptoms Of Overexp: HLTH HAZ:INFLAMMATION, DERMATITIS.
Med Cond Aggravated By Exp: NONE SPECIFIED BY MANUFACTURER.
Emergency/First Aid Proc: INGEST:CONT MD AT ONCE. EYE:FLUSH IMMED W/ PLENTY OF WATER FOR AT LST 15 MINS. CONT MD AT ONCE. SKIN:FLUSH IMMED W/ PLENTY OF WATER FOR AT LST 15MINS. REMOVE CONTAM CLTHG. CONT MD. WASH CLTHG BEFORE RE-USE. INHAL:MOVE INTO FRESH AIR. IF NOT BRTHG, GIVE ARTF RESP. IF BRTHG IS DFCLT, GIVE OXYGEN. CONT MD AT ONCE. NOTE TO MD:THERE IS NO SPECIFIC ANTIDOTE. TREATMENT OF OVEREXP SHOULD BE (SUPP DATA)
=====

=====
Precautions for Safe Handling and Use
=====

Steps If Matl Released/Spill: ELIM SOURCES OF IGNIT, PROVIDE ADEQ VENT & SUITABLE PROT CLTHG. COLLECT W/INERT ABSORB MATL & PLACE IN SUITABLE CNTNR FOR DISP. DISP OF CONTAM PROD & MATLS USED IN CLEANING UP SPILLS & LEAKS IN A MANNER APPRVD FOR THIS MATL.
Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.
Waste Disposal Method: DUE TO NATURE OF THIS PROD, DISP OF IT/RESIDUES THEREFROM SHOULD BE MADE IN COMPLIANCE W/FED, STATE & LOC ENVIRON LAWS. CONT YOUR SHIPLEY TECHNICAL REPRESENTATIVE FOR MORE INFO. IT IS YOUR RESPONSIBILITY TO VERIFY THAT ANY REC PROCS COMPLY W/(SUPDAT)

Precautions-Handling/Storing: CAUTION! COMBUSTIBLE LIQUID. STORE IN CLOSED, ORIGINAL CONTAINER IN A COOL, DRY AREA AT 50-90F. AVOID STORING LONGER THAN ONE YEAR.

Other Precautions: KEEP AWAY FROM ACIDS, OXIDANTS, HEAT & SOURCES OF IGNITION. AVOID SKIN CONTACT.

=====
Control Measures
=====

Respiratory Protection: THE SPECIFIC RESPIRATOR SELECTED MUST BE BASED ON AIRBORNE CONCENTRATION FOUND IN WORKPLACE & MUST NOT EXCEED WORKING LIMITS OF RESPIRATOR. THE RESPIRATOR MUST BE NIOSH/MSHA APPROVED.

Ventilation: PROVIDE GOOD GEN (MECH) ROOM VENT. SPECIAL LOC EXHST VENT IS REC AT POINTS WHERE VAPS CAN BE RELS INTO WORKPLACE AIR.

Protective Gloves: CHEMICAL RESISTANT GLOVES.

Eye Protection: CHEMICAL GOGGLES.

Other Protective Equipment: SUITABLE PROTECTIVE CLOTHING TO PREVENT SKIN CONTACT.

Work Hygienic Practices: PRACTICE GOOD PERSONAL HYGIENE TO PREVENT ACCIDENTAL EXPOSURE.

Suppl. Safety & Health Data: % VOLAT:100(WT). FIRST AID PROC:DIRECTED AT THE CONTROL OF SYMPTOMS & THE CLINICAL CONDITION. WASTE DISP METH:FEDERAL, STATE & LOCAL REGULATIONS FOR WASTEWATER DISCHARGE.

=====
Transportation Data
=====

=====
Disposal Data
=====

=====
Label Data
=====

Label Required: YES

Technical Review Date: 29DEC94

Label Date: 22DEC94

Label Status: G

Common Name: MICROPOSIT REMOVER 1165

Chronic Hazard: YES

Signal Word: WARNING!

Acute Health Hazard-Slight: X

Contact Hazard-Slight: X

Fire Hazard-Moderate: X

Reactivity Hazard-None: X

Special Hazard Precautions: COMBUSTIBLE. ACUTE:EYE & SKIN CONTACT CAN CAUSE IRRITATION, ITCHING, REDNESS, TEARING, BURNING, INFLAMMATION. INHALATION, INGESTION & SKIN ABSORPTION CAN CAUSE IRRITATION, HEADACHE, NAUSEA, VOMITING, CONFUSION, GIDDINESS. CHRONIC:PROLONGED, REPEATED CONTACT W/SKIN CAN CAUSE ITCHING, REDNESS, TEARING, BURNING, INFLAMMATION, DERMATITIS.

Protect Eye: Y

Protect Skin: Y

Protect Respiratory: Y

Label Name: SHIPLEY CO INC

Label Street: 455 FOREST ST

Label City: MARLBOROUGE

Label State: MA

Label Zip Code: 01752

Label Country: US

Label Emergency Number: 800-424-9300 (CHEMTREC)