



Substance key: SXR100615
Version 1

REVISION DATE: 06/26/2006
Print Date: 06/27/2006

Section 01 - Product Information

Identification of the company:	AZ Electronic Materials USA Corp. 70 Meister Avenue Somerville, NJ 08876 Telephone No.: 800-515-4164
Information on the substance/preparation	Product Safety: 908-429-3562
Emergency Tel. number:	800-424-9300 CHEMTREC

Trade name: **AZ® 1518 Photoresist IN (US)**

Section 02 - Composition information

Hazardous ingredients:

Chemical Name	CAS-no. (Trade secret no.)	Concentration [%]
1-Methoxy-2-propanol acetate	108-65-6	70.00 - 75.00
Diazonaphthoquinonesulfonic ester	68510-93-0	5.00 - 10.00

Non-hazardous ingredients:

Chemical Name	CAS-no. (Trade secret no.)	Concentration [%]
Cresol novolak resin	117520-84-0	20.00 - 25.00

Section 03 - Hazardous identification

Emergency overview: Amber-red liquid with characteristic odor., Partially dissolves in water leaving a floating viscous mass., OSHA combustible liquid; DOT flammable liquid., Irritating on contact or inhalation.

Expected route of entry

Skin contact: yes
Ingestion: no
Inhalation: yes
Eye contact: Contact with liquid and vapors.



Substance key: SXR100615
Version 1

REVISION DATE: 06/26/2006
Print Date: 06/27/2006

Skin absorption: yes

Health effects of exposure:

Component information:

Eye: Causes eye irritation. Skin: Causes skin irritation. Ingestion: May be harmful if swallowed. Inhalation: Single exposure unlikely to be hazardous. High vapor concentration causes irritation to the nose, throat, and lungs. Systemic Effects: No hazard in normal industrial use. Reproductive & birth defects: Exposures having no adverse effect on the mother should have no effect on the fetus.

1-Methoxy-2-propanol acetate (108-65-6)

1-Methoxy-2-propanol acetate (PGMEA) can cause skin, eye, and respiratory irritation. Extreme or prolonged exposure may cause gastric and central nervous system effects. Long term, high level exposure to PGMEA has resulted in adverse effects to the livers and kidneys of experimental animals. PGMEA is readily absorbed through intact skin.

Known effects on other illnesses: Preexisting skin, eye, and respiratory conditions may be aggravated.

Listed carcinogen: IARC: NO NTP: NO OSHA: NO

HMIS:

Health: 2 Flammability: 2 Reactivity: 0 Personal protection: X

NFPA:

Health: 2 Flammability: 2 Reactivity: 0 Special notice: NONE

Section 04 - First aid measures

After inhalation: Remove victim to fresh air. Consult physician.

After contact with skin: Immediately remove contaminated clothing. Flush affected area thoroughly with water. After flushing with water, remove residue with soap and water. If necessary, clean area with a cloth or paper towel wetted with acetone. Assure adequate ventilation. Dispose of cloth/towel in a suitable receptacle. Consult physician if irritation occurs or if irritation is extensive.

After contact with eyes: Immediately flush the eyes with large amounts of water, occasionally lifting the upper and lower eyelids, for at least 15 minutes. Seek medical attention immediately.

After ingestion: If person is conscious, give water or milk to dilute stomach

contents.
Never give anything by mouth to an unconscious person.
Consult physician.
Do not induce vomiting.

**Advice to doctor /
Treatment:**

Administer oxygen if there is difficulty in breathing.

Section 05 - Fire fighting measures

Flash point: 112 °F
Method: closed cup

Special fire fighting procedure: Use self-contained breathing apparatus and full protective clothing. Use water spray to cool drums in fire area.

Special hazards from the substance itself, its combustion products or from its vapours: Solvent vapors.
Emits toxic fumes under fire conditions.

Section 06 - Accidental release measures

Steps to be taken in case of spill or leak: Wearing appropriate personal protective equipment, contain spill, ventilate area of spill or leak, remove all sparking devices or ignition sources, collect onto inert absorbent, and place in a suitable container.

Section 07 - Handling and Storage

Advice on safe handling:

Keep away from heat and flame.
Avoid breathing vapors and contact with skin, eyes, and clothing.
Use only with adequate ventilation and proper protective eyewear, gloves, and clothing.
Wash thoroughly after handling.
Keep container closed.

Further information for storage conditions:

Store in original container.
Transport and store under dry conditions tightly closed.
May liberate combustible solvent vapors.

Section 08 - Exposure Control / personal protection

Respiratory protection: Chemical cartridge respirator recommended for exposures exceeding TLV.

Hand protection:	Chemical resistant gloves.
Eye protection:	Safety eyewear to protect against splashes.
Body protection:	Clothing suitable to prevent skin contact.
Additional advice on system design:	Use local exhaust ventilation.

Section 09 - Physical and chemical properties

Form:	Liquid
Color:	Clear, amber-red
Odor:	Strong, characteristic odor.
Density:	1 g/cm ³ 20 °C
Starts to boil:	from 145 °C
Evaporation number:	0.33 (PGMEA)
Vapor pressure:	2.6 Torr Method: calculated
Viscosity, dynamic:	approx. 35 mPas 20 °C
Loss on drying:	73 %

Section 10 - Stability and reactivity

Hazardous reactions:	Stable.
Hazardous polymerization:	Will not occur.
Conditions to avoid:	Avoid contact with oxidizing agents. Avoid contact with strong acids. Avoid contact with alkaline materials.

Section 11 - Toxicological information

Acute oral toxicity:	Based on data from components this material is considered, not harmful (rat acute oral LD ₅₀ > 5000 mg/kg).
Acute inhalation toxicity	

Based on data from components, this material is considered, not harmful (LC50 greater than 10,000 ppm or 200 mg/L), Based on component data, material is considered irritating to the respiratory tract.

Acute dermal toxicity: The acute toxicity via the dermal route of exposure, based on component data, suggest that this material should be considered not harmful (rabbit or rat dermal LD50 greater than 2000 mg/kg)

Skin irritation: Based on data from components, this material is considered a non-irritant; however, the product is considered to be a human skin irritant.

Eye irritation: Based on data from components, this material is considered to be a mild eye irritant.

1-Methoxy-2-propanol acetate (108-65-6)

Acute oral toxicity: LD50 rat (male)
8,500 mg/kg

1-Methoxy-2-propanol acetate (108-65-6)

Acute oral toxicity: LD50 rat (female)
10,000 mg/kg

1-Methoxy-2-propanol acetate (108-65-6)

Acute inhalation toxicity LC50 rat
> 4350 ppm

1-Methoxy-2-propanol acetate (108-65-6)

Acute dermal toxicity: LD50 rabbit
> 5,000 mg/kg

Section 12 - Ecological information

Biodegradability: No information.

Fish toxicity: Based on data from components, this material is classified as:, Not Harmful (LC50 > 100 mg/L).

Toxicity of aquatic invertebrates: Based on data from components, this material is classified as:, Not Harmful (EC50 greater than 100 mg/L).

Algae toxicity : No data available.

1-Methoxy-2-propanol acetate (108-65-6)

Fish toxicity: (Fathead minnow)
161 mg/l



Substance key: SXR100615
Version 1

REVISION DATE: 06/26/2006
Print Date: 06/27/2006

1-Methoxy-2-propanol acetate (108-65-6)
Toxicity of aquatic (Daphnia magna)
invertebrates: 400 mg/l

Section 13 - Disposal considerations

Product: Consult local, state, and federal regulations.

RCRA hazardous waste: RCRA number: D001
Yes -- If it becomes a waste as sold.

Section 14 - Transport information

Land transport

- *DOT:*
Not restricted

Sea transport

- *IMDG:*
UN-No: 1993
Proper technical name: FLAMMABLE LIQUIDS, N.O.S. contains (2-methoxy-1-methylethyl acetate)
Class: 3
Packaging group: III
Marine pollutant:
EmS: F-E, S-E
MFAG:
Labels: 3

Air transport

- *ICAO/IATA-DGR:*
UN/ID No.: UN 1993
Proper technical name: FLAMMABLE LIQUIDS, N.O.S. contains (2-methoxy-1-methylethyl acetate)
Class: 3
Packaging group: III
Labels: 3

Section 15 - Regulatory information



Substance key: SXR100615
Version 1

REVISION DATE: 06/26/2006
Print Date: 06/27/2006

TSCA Status:	All components of this product are listed on the TSCA Inventory.
SARA (section 311/312):	Reactive hazard: no Pressure hazard: no Fire hazard: yes Immediate/acute: yes Delayed/chronic: no
SARA 313 information:	This product is not subject to SARA Title III Section 313 reporting requirements under 40 CFR 372.
Volatile organic compounds:	Content VOC (g/l): 740 g/l Method: calculated

Section 16 - Other information

Label information

CAUTION!

COMBUSTIBLE LIQUID AND VAPOR HARMFUL IF SWALLOWED, INHALED OR ABSORBED THROUGH SKIN Contains material that, based on animal data, can cause skin, eye, and respiratory irritation. Prolonged or repeated overexposure may cause gastric and central nervous system effects.

Keep away from heat and flame. Avoid breathing vapor. Avoid contact with skin, eyes, and clothing. Use only with adequate ventilation, and proper protective eyewear, gloves, and clothing. Wash thoroughly after handling. Keep container closed.

In case of contact, flush eyes with plenty of water for 15 minutes. Get medical attention immediately. Flush affected skin areas with water, and wash with mild soap and water. Remove contaminated clothing. If INHALED, remove individual to fresh air. If breathing is difficult, give oxygen. If ingested, give water or milk to dilute stomach contents. Never give anything by mouth to an unconscious person. Get medical attention immediately for ingestion or breathing problems or if skin contact is extensive.

In case of fire, use water, alcohol resistant foam, dry chemical, or CO2.

If spilled, wear protective clothing, remove ignition sources, prevent sparks, and ventilate area. Absorb with inert material, collect, and place in a chemical waste container.

Keep sealed in original container. Store between 30 and 75 °F (-1 and 24 °C). Refrigerate whenever possible to extend shelf life. Allow product to reach ambient temperature prior to use. Empty container may contain harmful residue.

The solvent in this product is not photochemically reactive per Rule 102 of the California South Coast Air Quality Management District.

MATERIAL SAFETY DATA SHEET
AZ 1518 Photoresist IN (US)



Substance key: SXR100615
Version 1

REVISION DATE: 06/26/2006
Print Date: 06/27/2006

This information is supplied under the OSHA Hazard Communication Standard, 29 CFR 1910.1200, and is offered in good faith based on data available to us that we believe to be true and accurate. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable to the material. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate for that use. No warranty, express or implied, is made regarding the accuracy of this data, the hazards connected with the use of the material, or the results to be obtained from the use thereof. We assume no responsibility for damage or injury from the use of the product described herein. Data provided here are typical and not intended for use as product specifications. (R) and TM indicate trademarks of AZ Electronic Materials USA Corp., its business partners and suppliers.
