

Klean Strip Odorless Mineral Spirits

Revision: 12/18/2017

Supersedes Revision: 12/13/2017

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Klean Strip Odorless Mineral Spirits

Company Name: W. M. Barr
2105 Channel Avenue
Memphis, TN 38113

Phone Number: (901)775-0100

Web site address: www.wmbarr.com

Emergency Contact: 3E 24 Hour Emergency Contact (800)451-8346
Information: W.M. Barr Customer Service (800)398-3892

Intended Use: Paint, stain, and varnish thinning.

Product Code: GKSP94006P, QKSP94005, QKSP94205, GKSP94006, GKSP94214, CKSP94007, DKSP94007

2. HAZARDS IDENTIFICATION

Flammable Liquids, Category 3
Skin Corrosion/Irritation, Category 2
Specific Target Organ Toxicity (single exposure), Category 3
Aspiration Toxicity, Category 1



GHS Signal Word: **Danger**

GHS Hazard Phrases: H226: Flammable liquid and vapor.
H304: May be fatal if swallowed and enters airways.
H315: Causes skin irritation.
H336: May cause drowsiness or dizziness.

GHS Precaution Phrases: P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233: Keep container tightly closed.
P241: Use explosion-proof electrical/ventilating/lighting equipment.
P242: Use only non-sparking tools.
P243: Take precautionary measures against static discharge.
P261: Avoid breathing gas/mist/vapors/spray.
P264: Wash hands thoroughly after handling.
P271: Use only outdoors or in a well-ventilated area.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P235: Keep cool.

GHS Response Phrases: P301+310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P302+352: IF ON SKIN: Wash with plenty of soap and water.
P303+361+353: IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312: Call a POISON CENTER or doctor/physician if you feel unwell.
P321: Specific treatment see label.
P331: Do NOT induce vomiting.
P332+313: If skin irritation occurs, get medical advice/attention.
P362: Take off contaminated clothing and wash before re-use.

GHS Storage and Disposal Phrases: P403+233: Store container tightly closed in well-ventilated place.
P405: Store locked up.
P501: Dispose of contents/container according to local, state and federal regulations.

Klean Strip Odorless Mineral Spirits

Revision: 12/18/2017

Supersedes Revision: 12/13/2017

Hazard Rating System:

HEALTH	1
FLAMMABILITY	2
PHYSICAL	0
PPE	X



HMIS:

OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations.

Potential Health Effects
(Acute and Chronic):

Acute health effects

Eye contact: No known significant effects or critical hazards.

Inhalation: Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.

Skin contact: Causes skin irritation. Defatting to the skin.

Ingestion: Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

Medical Conditions Generally None known.

Aggravated By Exposure:

3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS #	Hazardous Components (Chemical Name)	Concentration
64742-47-8	Hydrotreated light distillate (petroleum, mineral spirits)	100.0 %

4. FIRST AID MEASURES

Emergency and First Aid
Procedures:

Inhalation:

If user experiences breathing difficulty, move to air free of vapors. Administer oxygen or artificial respiration until medical assistance can be rendered.

Skin contact:

Wash with soap and large quantities of water for at least 15 minutes. Seek medical attention if irritation from contact persists.

Eye contact:

Immediately flush eyes with water, remove any contact lens, continue flushing with water for at least 15 minutes. Get medical attention.

Ingestion:

Do not induce vomiting. Call your poison control center, hospital emergency room, or physician immediately.

Signs and Symptoms Of
Exposure:

Primary routes of exposure:

Inhalation, ingestion, and dermal.

Note to Physician:

Call your local poison control center for further instructions.

Klean Strip Odorless Mineral Spirits

Revision: 12/18/2017

Supersedes Revision: 12/13/2017

5. FIRE FIGHTING MEASURES

Flammability Classification:	NFPA Class II
Flash Pt:	> 105.80 F Method Used: TAG Closed Cup
Explosive Limits:	LEL: .6 UEL: 5.5
Autoignition Pt:	456.80 F
Suitable Extinguishing Media:	Use carbon dioxide, dry chemical powder, or foam.
Fire Fighting Instructions:	Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have been exposed to intense heat or flame.
Flammable Properties and Hazards:	No data available.

6. ACCIDENTAL RELEASE MEASURES

Steps To Be Taken In Case Material Is Released Or Spilled:	<p>Clean-up: Keep unnecessary people away, isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources, keep flares, smoking or flames out of hazard area.</p> <p>Small spills: Take up the spilled liquid with sand, earth, or other noncombustible absorbent material and place in a plastic container where applicable.</p> <p>Large spills: Dike far ahead of spill for later disposal.</p>
---	---

7. HANDLING AND STORAGE

Precautions To Be Taken in Handling:	Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.
Precautions To Be Taken in Storing:	Keep container tightly closed when not in use. Store in a cool, dry place. Do not store near flames or at elevated temperatures.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
64742-47-8	Hydrotreated light distillate (petroleum, mineral spirits)	No data.	TLV: 200 mg/m3	No data.
Respiratory Equipment (Specify Type):	For OSHA controlled work place and other regular users. Use only with adequate ventilation under engineered air control systems designed to prevent exceeding appropriate TLV. For occasional use, where engineered air control is not feasible, use properly maintained and properly fitted NIOSH approved respirator for organic solvent vapors. A dust mask does not provide protection against vapors.			
Eye Protection:	Safety glasses, chemical goggles or face shields are recommended to safeguard against potential eye contact, irritation, or injury. Contact lenses should not be worn while working with chemicals.			
Protective Gloves:	Wear impermeable gloves. Gloves contaminated with product should be discarded. Promptly remove clothing that becomes soiled with product.			
Other Protective Clothing:	Various application methods can dictate use of additional protective safety equipment,			

Klean Strip Odorless Mineral Spirits

Revision: 12/18/2017

Supersedes Revision: 12/13/2017

such as impermeable aprons, etc., to minimize exposure. Before reuse, thoroughly clean any clothing or protective equipment that has been contaminated by prior use. Discard any clothing or other protective equipment that cannot be decontaminated, such as gloves or shoes.

**Engineering Controls
(Ventilation etc.):**

Use only with adequate ventilation to prevent build-up of vapors. Open all windows and doors. Use only with a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea, or eye-watering -- Stop -- ventilation is inadequate. Leave area immediately.

**Work/Hygienic/Maintenance
Practices:**

A source of clean water should be available in the work area for flushing eyes and skin. Do not eat, drink, or smoke in the work area. Wash hands thoroughly after use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical States:	[] Gas [X] Liquid [] Solid
Appearance and Odor:	Colorless to light yellow Solvent odor
Melting Point:	-72.40 F
Boiling Point:	318.20 F - 354.20 F
Autoignition Pt:	456.80 F
Flash Pt:	> 105.80 F Method Used: TAG Closed Cup
Explosive Limits:	LEL: .6 UEL: 5.5
Specific Gravity (Water = 1):	0.78
Density:	6.5
Vapor Pressure (vs. Air or mm Hg):	3 MM HG at 25.0 C
Vapor Density (vs. Air = 1):	4.5 Air = 1
Evaporation Rate:	< 1 (BuAC=1)
Solubility in Water:	No data.
Solubility Notes:	Very slightly soluble in the following materials: cold water. (1.5 g/l)
Percent Volatile:	100.0 % by weight.
VOC / Volume:	780.0000 G/L
Additional Physical Information	Conductivity = <5 picosiemens/meter (unadditized)

10. STABILITY AND REACTIVITY

Stability:	Unstable [] Stable [X]
Conditions To Avoid - Instability:	Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas. Do not store with strong oxidizing agents.
Incompatibility - Materials To Avoid:	Incompatible with strong oxidizing agents.
Hazardous Decomposition or Byproducts:	Thermal decomposition may produce carbon monoxide and carbon dioxide.
Possibility of Hazardous Reactions:	Will occur [] Will not occur [X]
Conditions To Avoid - Hazardous Reactions:	No data available.

Klean Strip Odorless Mineral Spirits

Revision: 12/18/2017

Supersedes Revision: 12/13/2017

11. TOXICOLOGICAL INFORMATION

Toxicological Information:	In animal studies utilizing mineral spirits containing up to 22% aromatics indicated that the acute central nervous system effects are reversible. Based on existing animal studies, the potential for persistent effects is not clear.
Irritation or Corrosion:	Primary dermal irritation studies (four hour exposure) in rabbits utilizing mineral spirits containing less than 2% aromatics resulted in slight to moderate skin irritation. In humans, mineral spirits have produced slight to moderate skin irritation particularly with evaporation from the skin is prevented. Animal studies have demonstrated that mineral spirits produced mild respiratory tract irritation at elevated concentrations. Also, sensory respiratory tract irritation was evident by reduced breathing rates in the test animals in certain studies.
Symptoms related to Toxicological Characteristics:	Eye contact: Adverse symptoms may include the following: pain or irritation watering redness Inhalation: Repeated or prolonged overexposure to solvents can cause brain or other nervous system damage. The symptoms can include the loss of memory, the loss of intellectual capacity and the loss of coordination. Adverse symptoms may include the following: nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness Skin contact: Adverse symptoms may include the following: irritation redness dryness cracking Ingestion: Adverse symptoms may include the following: nausea or vomiting

Carcinogenicity/Other Information: ACGIH A4 - Not Classifiable as a Human Carcinogen.

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
64742-47-8	Hydrotreated light distillate (petroleum, mineral spirits)	n.a.	n.a.	A4	n.a.

12. ECOLOGICAL INFORMATION

General Ecological Information: This product has not been tested as a whole. Information below will be for individual ingredients.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose in accordance with applicable local, state, and federal regulations.

Klean Strip Odorless Mineral Spirits

Revision: 12/18/2017

Supersedes Revision: 12/13/2017

14. TRANSPORT INFORMATION

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Paint related material

DOT Hazard Class: 3 FLAMMABLE LIQUID

UN/NA Number: UN1263 Packing Group: III



Additional Transport Information:

The shipper may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

15. REGULATORY INFORMATION

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
64742-47-8	Hydrotreated light distillate (petroleum, mineral spirits)	No	No	No

This material meets the EPA [X] Yes [] No Acute (immediate) Health Hazard
 'Hazard Categories' defined [] Yes [X] No Chronic (delayed) Health Hazard
 for SARA Title III Sections [X] Yes [] No Fire Hazard
 311/312 as indicated: [] Yes [X] No Sudden Release of Pressure Hazard
 [] Yes [X] No Reactive Hazard

CAS #	Hazardous Components (Chemical Name)	Other US EPA or State Lists
64742-47-8	Hydrotreated light distillate (petroleum, mineral spirits)	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No

Additional Regulatory Information

This product is regulated by the United States Consumer Product Safety Commission and is subject to certain labeling requirements under the Federal Hazardous Substances Act. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS). The product label also includes other important information, including directions for use, and should always be read in its entirety prior to using the product.

16. OTHER INFORMATION

Revision Date: 12/18/2017
 Preparer Name: W.M. Barr EHS Department (901)775-0100
 Additional Information About This Product: No data available.

This Product:

Company Policy or Disclaimer:

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.

SAFETY DATA SHEET
Klean Strip Odorless Mineral Spirits

Revision: 12/18/2017

Supersedes Revision: 12/13/2017