
MSDS Number: C2475 \* \* \* \* Effective Date: 05/19/08 \* \* \* \* \* Supercedes: 08/17/05



# **CHLOROBENZENE**

### **1. Product Identification**

Synonyms: Monochlorobenzene; Chlorobenzol; Phenyl chloride; Benzene chloride CAS No.: 108-90-7 Molecular Weight: 112.56 Chemical Formula: C6H5Cl Product Codes: J.T. Baker: 5153, 5163, 9179 Mallinckrodt: 4419, 4426

# 2. Composition/Information on Ingredients

Ingredient	CAS No	Percent	Hazardous
Chlorobenzene	108-90-7	99 - 100%	Yes

### 3. Hazards Identification

**Emergency Overview** 

WARNING! FLAMMABLE LIQUID AND VAPOR. HARMFUL IF SWALLOWED OR INHALED. CAUSES IRRITATION TO SKIN, EYES AND RESPIRATORY TRACT. AFFECTS CENTRAL NERVOUS SYSTEM AND LIVER.

**SAF-T-DATA**<sup>(tm)</sup> Ratings (Provided here for your convenience)

------

Health Rating: 2 - Moderate (Life) Flammability Rating: 2 - Moderate Reactivity Rating: 1 - Slight Contact Rating: 3 - Severe Lab Protective Equip: GOGGLES & SHIELD; LAB COAT & APRON; VENT HOOD; PROPER GLOVES; CLASS B EXTINGUISHER Storage Color Code: Red (Flammable)

-----

### **Potential Health Effects**

\_\_\_\_\_

#### Inhalation:

Causes irritation to the respiratory tract. Symptoms may include coughing, shortness of breath. Affects central nervous system causing dizziness, incoordination and unconsciousness.

### Ingestion:

Causes irritation to the gastrointestinal tract. Symptoms may include nausea, vomiting and diarrhea. Toxic! May cause systemic poisoning with symptoms paralleling those of inhalation.

#### **Skin Contact:**

Causes irritation to skin. Symptoms include redness, itching, and pain. May be slowly absorbed through the skin with possible systemic effects.

### **Eye Contact:**

Vapors cause eye irritation. Splashes cause severe irritation, possible corneal burns and eye damage.

#### **Chronic Exposure:**

Prolonged or repeated skin exposure may cause dermatitis or skin burns. Prolonged or repeated exposure may cause liver, kidney, or lung damage.

### **Aggravation of Pre-existing Conditions:**

Persons with pre-existing skin, eye or central nervous system disorders, or impaired liver, kidney, or pulmonary function may be more susceptible to the effects of this substance.

### 4. First Aid Measures

#### Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

#### **Ingestion:**

Give large amounts of water to drink. Never give anything by mouth to an unconscious person. Get medical attention.

#### Skin Contact:

Immediately flush skin with plenty of soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse. **Eve Contact:** 

Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

### 5. Fire Fighting Measures

### Fire:

Flash point: 28C (82F) CC Autoignition temperature: 593C (1099F) Flammable limits in air % by volume: lel: 1.3; uel: 9.6 Flammable Liquid

### Explosion:

Above flash point, vapor-air mixtures are explosive within flammable limits noted above. Reactions with incompatibles may pose an explosion hazard. Vapors can flow along surfaces to distant ignition source and flash back. Sealed containers may rupture when heated. Sensitive to static discharge.

### Fire Extinguishing Media:

Dry chemical, foam or carbon dioxide. Water spray may be used to keep fire exposed containers cool, dilute spills to nonflammable mixtures, protect personnel attempting to stop leak and disperse vapors.

### **Special Information:**

In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode. This highly flammable liquid must be kept from sparks, open flame, hot surfaces, and all sources of heat and ignition. Combustion by-products include phosgene and hydrogen chloride gases.

### 6. Accidental Release Measures

Ventilate area of leak or spill. Remove all sources of ignition. Wear appropriate personal protective equipment as specified in Section 8. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Contain and recover liquid when possible. Use non-sparking tools and equipment. Collect liquid in an appropriate container or absorb with an inert material (e. g., vermiculite, dry sand, earth), and place in a chemical waste container. Do not use combustible materials, such as saw dust. Do not flush to sewer! If a leak or spill has not ignited, use water spray to disperse the vapors, to protect personnel attempting to stop leak, and to flush spills away from exposures. US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802.

J. T. Baker SOLUSORB® solvent adsorbent is recommended for spills of this product.

### 7. Handling and Storage

Protect against physical damage. Outside or detached storage is preferred. Inside storage should be in a standard flammable liquids storage room or cabinet. Separate from oxidizing materials. Storage and use areas should be No Smoking areas. Containers should be bonded and grounded for transfers to avoid static sparks. Containers of this material may be hazardous when empty since they retain product residues (vapors, liquid); observe all warnings and precautions listed for the product.

### 8. Exposure Controls/Personal Protection

#### **Airborne Exposure Limits:**

-OSHA Permissible Exposure Limit (PEL): 75 ppm (TWA)

-ACGIH Threshold Limit Value (TLV): 10 ppm (TWA)

### Ventilation System:

A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most recent edition, for details.

### Personal Respirators (NIOSH Approved):

If the exposure limit is exceeded and engineering controls are not feasible, a half-face organic vapor respirator may be worn for up to ten times the exposure limit, or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. A full-face piece organic vapor respirator may be worn up to 50 times the exposure limit, or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. For emergencies or instances where the exposure levels are not known, use a full-face piece positive-pressure, air-supplied respirator. WARNING: Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.

### **Skin Protection:**

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

#### **Eye Protection:**

Use chemical safety goggles and/or a full face shield where splashing is possible. Maintain eye wash fountain and quick-drench facilities in work area.

### 9. Physical and Chemical Properties

**Appearance:** Clear, colorless liquid. **Odor:** Faint, almond like odor. Solubility: Insoluble in water. **Specific Gravity:** 1.11 @ 20C/4C pH: No information found. % Volatiles by volume @ 21C (70F): 100 **Boiling Point:** 132C (270F) **Melting Point:** -45C (-49F) Vapor Density (Air=1): 3.9 Vapor Pressure (mm Hg): 11.8 @ 25C (77F) **Evaporation Rate (BuAc=1):** 1.1

### **10. Stability and Reactivity**

 Stability:

 Stable under ordinary conditions of use and storage.

 Hazardous Decomposition Products:

 May produce carbon monoxide, carbon dioxide, hydrogen chloride and phosgene when heated to decomposition.

 Hazardous Polymerization:

 Will not occur.

 Incompatibilities:

 Oxidizing agents, dimethyl sulfoxide, silver perchlorate, silver chromate.

 Conditions to Avoid:

 Heat, flames, ignition sources and incompatibles.

# **11. Toxicological Information**

For Chlorobenzene: Oral rat LD50: 1110 mg/kg; Inhalation rat LC50: 2965 ppm. Investigated as a tumorigen, mutagen, reproductive effector.

# **12. Ecological Information**

### **Environmental Fate:**

When released into the soil, this material may evaporate to a moderate extent. When released into the soil, this material is not expected to biodegrade. When released into the soil, this material may leach into groundwater. When released to water, this material is expected to quickly evaporate. When released into the water, this material is expected to have a half-life of less than 1 day. When released into water, this material is not expected to biodegrade. This material is not expected to significantly bioaccumulate. When released into the air, this material may be moderately degraded by reaction with photochemically produced hydroxyl radicals. When released into the air, this material is expected to have a half-life between 1 and 10 days.

### **Environmental Toxicity:**

The LC50/96-hour values for fish are between 10 and 100 mg/l. This material is expected to be slightly toxic to aquatic life.

### 13. Disposal Considerations

Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved incinerator or disposed in a RCRA approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

### **14. Transport Information**

```
Domestic (Land, D.O.T.)
```

Proper Shipping Name: RQ, CHLOROBENZENE Hazard Class: 3 UN/NA: UN1134 Packing Group: III Information reported for product/size: 52L

International (Water, I.M.O.)

\_\_\_\_\_

Proper Shipping Name: CHLOROBENZENE Hazard Class: 3 UN/NA: UN1134 Packing Group: III Information reported for product/size: 52L

International (Air, I.C.A.O.)

\_\_\_\_\_

Proper Shipping Name: CHLOROBENZENE Hazard Class: 3 UN/NA: UN1134 Packing Group: III Information reported for product/size: 52L

# **15. Regulatory Information**

-----\Chemical Inventory Status - Part 2\-------Canada--Korea DSL NDSL Phil. Ingredient Chlorobenzene (108-90-7) Yes Yes No Yes Chlorobenzene (108-90-7) ------\Federal, State & International Regulations - Part 1\-------SARA 302- ----SARA 313-----RQ TPQ List Chemical Catg. Ingredient -----Yes No \_\_\_ No No Chlorobenzene (108-90-7) -----\Federal, State & International Regulations - Part 2\------RCRA- -TSCA-CERCLA 261.33 8(d) -------100 U037 Yes Ingredient \_\_\_\_\_ Chlorobenzene (108-90-7) Chemical Weapons Convention: No TSCA 12(b): Yes CDTA: Yes SARA 311/312: Acute: Yes Chronic: Yes Fire: Yes Pressure: No Reactivity: No (Pure / Liquid)

Australian Hazchem Code: 2Y Poison Schedule: None allocated. WHMIS: This MSDS has been prepared account

This MSDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

## 16. Other Information

NFPA Ratings: Health: 2 Flammability: 3 Reactivity: 0 Label Hazard Warning: WARNING! FLAMMABLE LIQUID AND VAPOR. HARMFUL IF SWALLOWED OR INHALED. CAUSES IRRITATION TO SKIN, EYES AND RESPIRATORY TRACT. AFFECTS CENTRAL NERVOUS SYSTEM AND LIVER. Label Precautions: Keep away from heat, sparks and flame. Avoid breathing vapor. Keep container closed. Wash thoroughly after handling. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Label First Aid: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If swallowed, give large amounts of water to drink. Never give anything by mouth to an unconscious person. In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Wash clothing before reuse. In all cases, get medical attention. **Product Use:** Laboratory Reagent. **Revision Information:** No Changes. **Disclaimer:** Mallinckrodt Baker, Inc. provides the information contained herein in good faith but makes no

representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose. MALLINCKRODT BAKER, INC. MAKES NO

REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR THE PRODUCT TO WHICH THE INFORMATION REFERS. ACCORDINGLY, MALLINCKRODT BAKER, INC. WILL NOT BE RESPONSIBLE FOR DAMAGES RESULTING FROM USE OF OR RELIANCE UPON THIS INFORMATION.

**Prepared by:** Environmental Health & Safety Phone Number: (314) 654-1600 (U.S.A.)