

Material Name: SULFUR HEXAFLUORIDE SDS ID: MAT22300

## \* \* \* Section 1 - PRODUCT AND COMPANY IDENTIFICATION \* \* \*

## Material Name: SULFUR HEXAFLUORIDE

#### **Manufacturer Information**

MATHESON TRI-GAS, INC. General Information: 1-800-416-2505

150 Allen Road, Suite 302 Emergency #: 1-800-424-9300 (CHEMTREC)

Basking Ridge, NJ 07920 Outside the US: 703-527-3887 (Call collect)

## **Chemical Family**

inorganic, gas

### **Synonyms**

MTG MSDS 81; SULFUR FLUORIDE; SULPHUR HEXAFLUORIDE; ELEGAS; UN 1080; F6S; RTECS: WS4900000

#### **Product Use**

industrial

## **Usage Restrictions**

none known

## \* \* \* Section 2 - HAZARDS IDENTIFICATION \* \* \*

#### **EMERGENCY OVERVIEW**

Color: colorless

Physical Form: gas

Odor: odorless

Health Hazards: difficulty breathing

Physical Hazards: Containers may rupture or explode if exposed to heat.

Material Name: SULFUR HEXAFLUORIDE SDS ID: MAT22300

#### POTENTIAL HEALTH EFFECTS

#### Inhalation

**Short Term:** nausea, vomiting, difficulty breathing, dizziness, fatigue, emotional disturbances, tingling sensation,

suffocation, convulsions, coma

Long Term: no information on significant adverse effects

Skin

Short Term: frostbite

Long Term: no information is available

Eye

Short Term: frostbite

Long Term: no information is available

Ingestion

Short Term: no information on significant adverse effects

Long Term: no information is available

## \* \* \* Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS \* \* \*

CAS	Component	Percent
2551-62-4	SULFUR HEXAFLUORIDE	100

#### **Component Related Regulatory Information**

This product may be regulated, have exposure limits or other information identified as the following: Fluorides.

## \* \* \* Section 4 - FIRST AID MEASURES \* \* \*

#### Inhalation

If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.

Material Name: SULFUR HEXAFLUORIDE SDS ID: MAT22300

#### Skin

If frostbite or freezing occur, immediately flush with plenty of lukewarm water (105-115 F; 41-46 C). DO NOT USE HOT WATER. If warm water is not available, gently wrap affected parts in blankets. Get immediate medical attention.

### **Eyes**

Flush eyes with plenty of water.

### Ingestion

If a large amount is swallowed, get medical attention.

#### **Note to Physicians**

For inhalation, consider oxygen.

## \* \* \* Section 5 - FIRE FIGHTING MEASURES \* \* \*

See Section 9 for Flammability Properties

NFPA Ratings: Health: 1 Fire: 0 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

## Flammable Properties

Negligible fire hazard. Containers may rupture or explode if exposed to heat.

#### **Extinguishing Media**

carbon dioxide, regular dry chemical

Large fires: Use regular foam or flood with fine water spray.

## **Unsuitable Extinguishing Media**

None known.

### **Protective Equipment and Precautions for Firefighters**

Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.

Material Name: SULFUR HEXAFLUORIDE SDS ID: MAT22300

## **Fire Fighting Measures**

Move container from fire area if it can be done without risk. Cool containers with water spray until well after the fire is out. Stay away from the ends of tanks. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. For tank, rail car or tank truck, evacuation radius: 800 meters (1/2 mile). Use extinguishing agents appropriate for surrounding fire. Cool containers with water spray until well after the fire is out. Apply water from a protected location or from a safe distance. Do not get water directly on material. Reduce vapors with water spray. Avoid inhalation of material or combustion by-products. Stay upwind and keep out of low areas. Consider downwind evacuation if material is leaking.

#### **Thermal Decomposition Products**

Combustion: fluorinated compounds, oxides of sulfur, sulfur compounds, hydrogen fluoride, hydrogen sulfide

\* \* \* Section 6 - ACCIDENTAL RELEASE MEASURES \* \* \*

### Occupational spill/release

Stop leak if possible without personal risk. Keep unnecessary people away, isolate hazard area and deny entry. Stay upwind and keep out of low areas.

\* \* \* Section 7 - HANDLING AND STORAGE \* \* \*

## **Handling Procedures**

Avoid breathing gas. Use only with adequate ventilation.

#### **Storage Procedures**

Store and handle in accordance with all current regulations and standards. Store below 49 C. Avoid shock. Store in a well-ventilated area. Store in a tightly closed container. Keep separated from incompatible substances. Secure to prevent tipping. Keep away from heat, sparks and flame. Store in a cool, dry place. Subject to storage regulations: U.S. OSHA 29 CFR 1910.101.

Page 4 of 10 Issue Date: 12/15/2009 Revision: 1.0200 Print Date: 2/8/2010

Material Name: SULFUR HEXAFLUORIDE SDS ID: MAT22300

## \* \* \* Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION \* \* \*

### **Component Analysis**

#### **SULFUR HEXAFLUORIDE (2551-62-4)**

ACGIH: 1000 ppm TWA

OSHA (final): 1000 ppm TWA; 6000 mg/m3 TWA

OSHA (vacated): 1000 ppm TWA; 6000 mg/m3 TWA

NIOSH: 1000 ppm TWA; 6000 mg/m3 TWA

#### **Component Biological Limit Values**

#### **SULFUR HEXAFLUORIDE (2551-62-4)**

ACGIH: Fluorides in urine: 3 mg/g creatinine, prior to shift (B,Ns); Fluorides in urine: 10 mg/g creatinine,

end of shift (B,Ns)

#### Ventilation

Provide local exhaust ventilation system. Ensure compliance with applicable exposure limits.

#### PERSONAL PROTECTIVE EQUIPMENT

#### Eyes/Face

For the gas: Eye protection not required, but recommended. For the liquid: Wear splash resistant safety goggles. Contact lenses should not be worn. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

## **Protective Clothing**

For the gas: Protective clothing is not required. For the liquid: Wear appropriate protective, cold insulating clothing.

#### Glove Recommendations

Wear insulated gloves.

#### **Protective Materials**

leather

#### **Respiratory Protection**

Under conditions of frequent use or heavy exposure, respiratory protection may be needed.

**SDS ID: MAT22300** 

**Material Name: SULFUR HEXAFLUORIDE** 

Respiratory protection is ranked in order from minimum to maximum.

Consider warning properties before use.

#### For Unknown Concentrations or Immediately Dangerous to Life or Health -

Any supplied-air respirator with a full facepiece that is operated in a pressure-demand or other positive-pressure mode in combination with an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive-pressure mode.

Any self-contained breathing apparatus that has a full facepiece and is operated in a pressure-demand or other positive-pressure mode.

# \* \* \* Section 9 - PHYSICAL AND CHEMICAL PROPERTIES \* \* \*

Physical State:	Gas	Appearance:	Not available		
Color:	colorless	Physical Form:	gas		
Odor:	odorless	Odor Threshold:	Not available		
Melting/Freezing Point:	-50.5 °C	Boiling Point:	63.9 °C @ 101.3 kPa		
Flash Point:	not flammable	Decomposition:	Not available		
LEL:	Not available	UEL:	Not available		
Vapor Pressure:	16548 mmHg @ 20 °C	Henry's Law Constant:	4.52		
Vapor Density (air = 1):	5.1	Specific Gravity (water=1):	1.68		
Water Solubility:	slightly soluble	KOW:	47.867		
Log KOW:	see Section 12	KOC:	195 (estimated)		
Auto Ignition:	Not available	Viscosity:	0.0156 cP @ 25 °C		
Sublimation Point:	-63.9 °C	Volatility:	100 %		
Volatility by Volume:	100 %	Molecular Weight:	146.06		
Molecular Formula:	F6-S				

#### **Solvent Solubility**

<b>Soluble:</b> alcohol,	ether,	potassium	hydroxide	solutions,	transformer	OII

Slightly Soluble: ethanol

Material Name: SULFUR HEXAFLUORIDE SDS ID: MAT22300

Insoluble: hydrochloric acid, ammonia

## \* \* \* Section 10 - STABILITY AND REACTIVITY \* \* \*

### **Chemical Stability**

Stable at normal temperatures and pressure.

#### **Conditions to Avoid**

Protect from physical damage and heat. Containers may rupture or explode if exposed to heat.

#### **Materials to Avoid**

combustible materials, metals, oxidizing materials

Combustion: fluorinated compounds, oxides of sulfur, sulfur compounds, hydrogen fluoride, hydrogen sulfide

### **Possibility of Hazardous Reactions**

Will not polymerize.

## \* \* \* Section 11 - TOXICOLOGICAL INFORMATION \* \* \*

### Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and no selected endpoints have been identified.

#### **Component Carcinogenicity**

#### **SULFUR HEXAFLUORIDE (2551-62-4)**

**ACGIH:** A4 - Not Classifiable as a Human Carcinogen

#### **Irritation**

No human or animal test data available.

#### **Medical Conditions Aggravated by Exposure**

None known.

#### **Tumorigenic**

No data available.

Material Name: SULFUR HEXAFLUORIDE SDS ID: MAT22300

### Mutagenic

No data available.

### **Reproductive Effects**

No data available.

## \* \* \* Section 12 - ECOLOGICAL INFORMATION \* \* \*

### **Component Analysis - Aquatic Toxicity**

No LOLI ecotoxicity data are available for this product's components.

## \* \* \* Section 13 - DISPOSAL CONSIDERATIONS \* \* \*

## **Disposal Methods**

Dispose in accordance with all applicable regulations.

### **Component Waste Numbers**

The U.S. EPA has not published waste numbers for this product's components.

## \* \* \* Section 14 - TRANSPORT INFORMATION \* \* \*

#### **US DOT Information**

Shipping Name: Sulfur hexafluoride

UN/NA #: UN1080 Hazard Class: 2.2

Required Label(s): 2.2

### **TDG Information**

Shipping Name: Sulfur hexafluoride

UN #: UN1080 Hazard Class: 2.2

Required Label(s): 2.2

Material Name: SULFUR HEXAFLUORIDE SDS ID: MAT22300

## \* \* \* Section 15 - REGULATORY INFORMATION \* \* \*

### **U.S. Federal Regulations**

None of this products components are listed under SARA Sections 302/304 (40 CFR 355 Appendix A), SARA Section 311/312 (40 CFR 370.21), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), or require an OSHA process safety plan.

#### SARA 311/312

Acute Health: Yes Chronic Health: No Fire: No Pressure: Yes Reactive: No

### **U.S. State Regulations**

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA	RI
SULFUR HEXAFLUORIDE	2551-62-4	Yes	Yes	Yes	Yes	Yes	Yes

Not regulated under California Proposition 65

#### **Canada WHMIS**

The following components are identified under the Canadian Hazardous Products Act Ingredient Disclosure List:

#### **SULFUR HEXAFLUORIDE (2551-62-4)**

1 %

## **Component Analysis - Inventory**

Component	CAS	US	CA	EU	AU	PH	JP	KR	CN	NZ
SULFUR HEXAFLUORIDE	2551-62-4	Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	Yes

Page 9 of 10 Issue Date: 12/15/2009 Revision: 1.0200 Print Date: 2/8/2010

Material Name: SULFUR HEXAFLUORIDE SDS ID: MAT22300

## \* \* \* Section 16 - OTHER INFORMATION \* \* \*

### Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU -Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CN - China; CPR -Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LOLI - List Of LIsts™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR -New Jersey Trade Secret Registry: NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH - Philippines; RCRA - Resource Conservation and Recovery Act; RID -European Rail Transport; RTECS - Registry of Toxic Effects of Chemical Substances®; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US -**United States** 

#### Other Information

Matheson Tri-Gas, Inc. makes no express or implied warranties, guarantees or representations regarding the product or the information herein, including but not limited to any implied warranty or merchantability or fitness for use. Matheson Tri-Gas, Inc. shall not be liable for any personal injury, property or other damages of any nature, whether compensatory, consequential, exemplary, or otherwise, resulting from any publication, use or reliance upon the information herein.

End of Sheet MAT22300

Page 10 of 10 Issue Date: 12/15/2009 Revision: 1.0200 Print Date: 2/8/2010